



ICE-Trade sa
International Conveyor Equipment & Trading

Passage de la Poste 3 – 2
B – 7700 Mouscron
Belgium

Tel. + 32.56.48 18 80
Fax + 32.56.48 18 88
info@ice-trade.com
www.ice-trade.com

ICE-Trade ® Sidewall Buffing Machine



The ICE-Trade Sidewall Buffing Machine, ITSwBM, is developed to grind the bases of the sidewalls. The ITSwBM can buff sidewalls from S 40 till S 400.

The speed where the sidewall is going through the ITSwBM is approx. 3 m/min.

Against that speed it is impossible to grind sidewalls by hand !

The sidewall cannot be transported faster through the ITSwBM as this is the optimum speed to achieve a good buffed surface for bonding the sidewalls.



ICE-Trade sa

International Conveyor Equipment & Trading

Tel. + 32.56.48 18 80

Fax + 32.56.48 18 88

info@ice-trade.com

www.ice-trade.com

Technical specs

Type	ITCBM
Length	2 m
Width	0,65 m
Height	1,2 m
Weight	500 kg
Belt speed	approx. 3 m/min
Noise	< 70 dB (A)
Dust suction (diameter)	100 mm
Tension	415 V
Phases	3+N+E
Amps	16 A
Engine conveyor belt	0,25 kW
Engine grinding axle	3 kW

Operation of the ITSwBM is simple and easy.

The average setting time for another type of sidewall is approx. 1 minute.

A dust suction system, which is supplied along, sucks the rubber dust from below the grinding wheels.



The grinding wheels, Vane Wheels, covered with SSG ® tungsten carbide grit ensure a long lifetime.

Furthermore, because of its shape, and the power of the dust suction system, the temperature remains always low, to guarantee an optimum bonding result.



ICE-Trade sa
International Conveyor Equipment & Trading

Tel. + 32.56.48 18 80
Fax + 32.56.48 18 88
info@ice-trade.com
www.ice-trade.com

All the top parts are made from stainless steel, as also the machine covers. The frame, from steel is painted with 2 layers of 2 component epoxy base paint and finished with 2 layers of high quality 2 component acryl paint.



The grinding result :



For further information, please contact us.