



ICE-Trade s.a.

International Conveyor Equipment & Trading

Passage de la Poste 3-2
B-7700 Mouscron
Belgium

Tel. + 32.56.48 18 80

Fax + 32.56.48 18 88

info@ice-trade.com

www.ice-trade.com

ICE-Trade ® Snow Shovel Blades



Rubber Qualities

| Type | Quality | Density +/- 0,05 | Hardness Shore A +/- 5° | Break strength daN/cm ² | Elongation at break min. % | Abrasion mm ³ / 5N DIN 53516 | Color |
|---------------|---------|---------------------|-------------------------------|--|----------------------------------|---|-------|
| Crib 80 Black | Natural | 1,20 | 82 | 170 | 400 | 100 | Black |
| Perf Bi Shore | Natural | 1 layer | Perf 80 | 1 layer | Perf 60 | | Black |

Polyurethane Quality

| Properties | Standard | |
|---|------------------------|----------|
| Hardness | DIN 53505 | 80 |
| Density | DIN 53749 | 1,21 |
| Tear resistance - without nick - with nick | DIN 53515 DIN 53515 | 95 39 |
| Tensile strength | DIN 53504 | 41 |
| Elongation at break | DIN 53504 | 525 |
| Rebound resilience | DIN 53512 | 44 |
| Compression set at 25% compression during 22 h. at 70° C. | DIN 53517 | 19 |
| Abrasion resistance | DIN 53516 | 19 |

Standard Lengths

| mm. |
|------|
| 3000 |
| 3250 |
| 3500 |
| 3750 |
| 4000 |
| 4250 |
| 4500 |
| 4750 |
| 5000 |

Cross Sections

| mm. |
|----------|
| 200 x 30 |
| 250 x 30 |
| 300 x 30 |
| 200 x 35 |
| 250 x 35 |
| 300 x 35 |
| 200 x 40 |
| 250 x 40 |
| 300 x 40 |
| 200 x 50 |
| 250 x 50 |
| 300 x 50 |

Other dimensions are available on request.

The ICE-Trade Snow Shovel Blades in rubber are a stock item.